

HELLIGO PRODUCTS

Controller box with cloud device management system

Innovation designed for temperature and humidity controlled rooms that can be used in a variety of businesses.

Spec Sheet for model

SMART-AC-MID24-DW

HLG-SMART-AC-QWL

Helligo Member

<https://nest.helligo.com>



Technical Specifications

Features	SMART-AC-MID24-DW	HLG-SMART-AC-QWL
Air conditioner operation supports	2 Unit	4 Unit
Capacity air conditioner supports	up to 60,000 BTU	up to 192,000 BTU
Dimensions (Width x Height x Depth)	22.5 x 30 x 10 cm	22.5 x 30 x 10 cm
Processor	Microcontroller	Microcontroller
Power Input	220VAC 50Hz (±10%)	220VAC 50Hz (±10%)
Power / Current Output	Socket 1 : 7A Socket 2 : 7A	Socket 1 : 5A Socket 2 : 5A Socket 3 : 5A Socket 4 : 5A
Display	TFT LCD	TFT LCD
Temperature and humidity Sensor	DHT22	DHT22
Dry Contact	6 Channel	7 Channel
Network Interface supports	2.4 GHz WiFi Module Internet Sim Card Module 10/100 Base Ethernet Module	2.4 GHz WiFi Module Internet Sim Card Module 10/100 Base Ethernet Module
Controller Mode	Manual / Automatic	Manual / Automatic
Controller Management	Front button / Cloud Management	Front button / Cloud Management
Fire suppression system supports	Yes	Yes

Recommended support and services

Helligo warranty plan for critical systems on your devices. Consulting and deployment offerings are also available. Contact your Helligo representative nearby areas for more information. Availability and terms of Helligo services, visit www.helligo.com